

# InnoOSR

#### Full Recovery, Just One Click Away

Bring unbeatable convenience and speed to image recovery with Innodisk's exclusive InnoOSR series of flash storage products

innodisk

#### **Next-Level Firmware-Level Recovery**

InnoOSR's patented firmware technology enables truly next-level recovery ideal for applications that can afford little downtime. With a single click, on-site personnel can trigger a full firmware-level recovery – avoiding all pitfalls with software-level recovery – and bring the system back online in no time. Available in all key form factors and featuring Innodisk's trademark hardware and firmware technologies, the InnoOSR series is ready to upgrade any application to the future of one-click recovery.

## One-click recovery in three steps

- 1. Launch the InnoOSR tool
- 2. Create a backup image
- 3. Launch recovery with a hardware trigger

#### Firmware-level reliability

InnoOSR's firmware takes care of the entire recovery operation with LBA to LBA recovery – bypassing any software problems and allowing compatibility with any system.



#### Rock-bottom maintenance costs

Requires no expensive software and demands minimum technical expertise – a click is all it takes to recover.

### No-fuss system implementation

Utilizing standard form factors with pin headers, operators can effortlessly implement InnoOSR's powerful functionality in any application.







Model name	2.5" SATA 3TO7		M.2 2242 3TO7	M.2 2280 3TO7	
Interface	3rd generation SATA				
Flash type	Kioxia Industrial 3D TLC				
Capacity	32 GB -2 TB		32 GB - 512 GB	64 GB - 2 TB	
Max. channels	4 channels				
Sequential R/W (MB/sec, max.)*	545 / 335		500/330	560/340	
4 KB random (QD32) R/W (KIOPS)*	79/69		57/69	81/74	
Max. power consumption	3.5 W		1.5 W	2.1 W	
Thermal sensor					
ATA security	Supported				
iSMART					
Dimensions (WxLxH)	69.85 x 100 x 9.5 mm	Vertical pin headers 22 x 42/80 x 8.5 mm Horizontal pin headers 22 x 43.5/81.5 x 3.6 mm			
Operation temperature	Standard temp.: 0°C - 70 °C / Wide temp.: -40°C - 85 °C				
Note	*: Performance results are from out-of-box devices tested with CDM 5.1.2 as data disk.				



©2020 June. Innodisk Corporation

Headquarters Innodisk Corporation

E-mail : sales@innodisk.com