

Datasheet

U.2 SSD 4TS2-P series

- PCIe Gen 4x4, NVMe 1.4
- Excellent data transfer speed
- Heat-spreading design
- LDPC ECC engine supported.
- End-to-end Data Path Protection
- High capacity & ultra-speed



Introduction


Innodisk U.2 SSD 4TS2-P is an NVMe Express SSD designed as PCIe SFF-8639 module with PCIe interface and 3D TLC NAND Flash. U.2 SSD 4TS2-P supports PCIe Gen 4x4, and it is compliant with NVMe 1.4 providing excellent performance. With sophisticated error detection and correction (ECC) functions, the module can ensure full End-to-end Data Path Protection that secures the data transmission between host system and NAND Flash.

Innodisk U.2 SSD 4TS2-P provides ultra-speed and high IOPS and offers maximum capacity up to 6.4TB, making the SSD optimal for server and heavy data workload applications.

U.2 SSD

4TS2-P series

Diagram



Contact us for more information about the U.2 SSD 4TS2-P.

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan
Tel: +886-2-7703-3000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2024 Innodisk Corporation.
All right reserved. Specifications are subject to change without prior notice.

20240821

Interface	PCIe Gen 4 x4
Flash Type	3D TLC
P/E cycle	3,000
Capacity	400GB~6.4TB
Max. Channels	8
Sequential R/W (MB/sec, max.)	7150/6100
Max. Power Consumption	12.6W
Thermal Sensor	√
External DRAM buffer	√
H/W Write Protect	NA
iCell	NA
Dimension (WxLxH)	69.85 X 100.0 X 6.9 mm
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Working Temperature: ST 0°C ~ +70°C, ; WT -40°C ~ +85°C Storage Temperature: -40°C ~ +85°C MTBF: 3 million hours

Ordering Information

Operation Temp.	400GB	800GB	1.6TB	3.2TB	6.4TB
Standard Grade (0°C ~ +70°C)	DSEU2-400DP1KCAEF	DSEU2-800DP1KCAEF	DSEU2-1T6DP1KCAEF	DSEU2-3T2DP1KCAEF	DSEU2-6T4DP1KCAEF
Industrial Grade (-40°C ~ +85°C)	DSEU2-400DP1KWAEF	DSEU2-800DP1KWAEF	DSEU2-1T6DP1KWAEF	DSEU2-3T2DP1KWAEF	DSEU2-6T4DP1KWAEF